

VERSION OF AMENDMENTS SHOWING MARKINGS

1. (Currently Amended) A furniture frame comprising:
 - a first section having a first side and a second side, said first section having at least one wheel rotatably secured thereto and at least one pivotal support member secured thereto for supporting said first section;
 - a prop bar fixedly secured to said at least one pivotal supporting member;
 - a second section connected to said first section, said second section having a first side and a second side and including at least one support member for supporting said second section; and
 - at least one catch member fixedly secured to one of said ~~side~~ sides of said second section, said catch member having at least one prop bar engaging notch for engaging receiving a portion of said prop bar thereon to support said furniture frame in a couch condition.
2. (Previously presented) The furniture frame of claim 1 wherein said first section comprises a backrest section and said second section comprises a seat section.
3. (Original) The furniture frame of claim 1 wherein said second section is connected to said first section through the engagement of a protruding member located on said first side of said first section with a slot located on the first side of the second section and a protruding member located on said second side of said first section with a slot located on said second side of said second section.

4. (Original) The furniture frame of claim 1 wherein said at least one wheel comprises a first wheel and a second wheel rotatably secured to said first section.
5. (Previously presented) The furniture frame of claim 1 wherein said at least one support member of said first section comprises a first support member secured to said first side of said first section and a second support member secured to said second side of said first section for supporting said first section.
6. (Original) The furniture frame of claim 1 wherein said at least one support member of said second section comprises a first support member secured to said first side of said second section and a second support member secured to said second side of said second section for supporting said second section.
7. (Original) The furniture frame of claim 1 wherein said at least one catch member comprises a first catch member secured to an interior surface of said first side of said second section and a second catch member secured to an interior surface of said second side of said second section.
8. (Currently Amended) The furniture frame of claim 1 wherein said at least one catch member having at least one prop bar engaging notch comprises a catch member having a first prop bar engaging notch and a second prop bar engaging notch for engaging receiving a portion of said prop bar thereon to support said furniture frame in a couch condition.

9. (Currently Amended) The furniture frame of claim 1 including at least one stop member located on the side of the first section in a fixed condition for limiting the movement of the support member of the first section when the furniture frame is in the bed position.

10. (Original) The furniture frame of claim 1 wherein the first side and the second side of the first section comprises a L-shape configuration.

11. (Currently Amended) A furniture frame comprising:

a first section having a first side and a second side, each of the sides of said first section having a pivotal support member connected thereto for supporting the first section;

at least one wheel rotatably secured to said first section;

a prop bar fixedly secured to said pivotal support members of said first section;

a second section connected to said first section, said second section having a first side and a second side with each of said sides of said second section having a support member for supporting said second section; and

at least one catch member fixedly secured to one of said ~~side~~ sides of said second section, said catch member having at least one prop bar engaging notch for engaging receiving a portion of said prop bar thereon to support said furniture frame in a couch condition.

12. (Original) The furniture frame of claim 11 wherein said first section comprises a backrest section and said second section comprises a seat section.

13. (Original) The furniture frame of claim 12 wherein said at least one wheel comprises a first wheel and a second wheel rotatably secured to said backrest section.

14. (Original) The furniture frame of claim 12 wherein said seat section is connected to said backrest section through the engagement of a protruding member located on said first side of said backrest section with a slot located on the first side of the seat section and a protruding member located on said second side of said backrest section with a slot located on said second side of said seat section.

15. (Original) The furniture frame of claim 12 wherein said at least one catch member comprises a first catch member secured to an interior surface of said first side of said seat section and a second catch member secured to an interior surface of said second side of said seat section.

16. (Currently Amended) The furniture frame of claim 12 wherein said at least one catch member having at least one prop bar engaging notch comprises ~~said~~ a catch member having a first prop bar engaging notch and a second prop bar engaging notch with each notch for ~~engaging~~ receiving a portion of said prop bar thereon to support said furniture frame in a couch condition.

17. (Original) The furniture frame of claim 12 wherein the backrest section comprises a L-shaped backrest section.

18. (Original) A method of converting a furniture frame from a bed position to a couch position comprising the steps of:

lifting a front edge of a seat section of the furniture frame in the bed position;

bringing a prop bar connected to at least one backrest support member and a notch of a catch member located on the side of the seat section into proximity;

raising the front edge of the seat section to allow the backrest support member and a portion of a prop bar to engage the notch of the seat section; and

lowering the front edge of the seat section to trap the portion of the prop bar to the notch of the seat section to maintain said frame in the couch position.

19. (Previously presented) The method of claim ~~46~~ 18 including the step of lifting said prop bar from said notch of the seat section to a further notch of said seat section to adjust the furniture frame in the couch position.

20. (Original) A method of converting a furniture frame from a couch position to a bed position comprising the steps of:

raising a front edge of a seat section of the furniture frame in the couch position;

disengaging a prop bar from a notch of a catch member located on the side of the seat section;

moving a backrest support member away from the catch member of the seat section; and

lowering the front edge of the seat section of the frame in the bed